

Item \ Model	LP1330-1	LP1330-2	LP1330-3	LP1330-4	LP1330-5
Output Voltage	+ 15V	+ 18V	+ 24V	+ 30V	+ 48V
Output Rating	2.2A	1.83A	1.38A	1.1A	0.69A
Current Limit Tolerance	±5%				
Input Voltage	90~264 VAC				
Input Frequency	47 ~63 Hz				
Input Current (max.)	1.5A:115VAC / 0.75A:230VAC				
Inrush Current (max.)	30A:115VAC / 60A:230VAC				
Line Regulation	±0.2%				
Load Regulation	±0.2%				
Ripple & Noise (max.)	150m Vp-p	180m Vp-p	240m Vp-p	300m Vp-p	480m Vp-p
Efficiency (typ.)	78%	78%	80%	80%	80%
Over-Voltage Protection	AUTO Recovery				
Short-circuit Protection	AUTO Recovery				
Operating Temperature	0°C ~ 50°C				
Storage Temperature	- 40 °C ~ 85°C				
Safety	MEET EN60950 UL1950 CSA22.2 NO.950 FCC PART 15 CLASS B PERFORMANCE CISPER 22 CLASS B (EN55022) PERFORMANCE				
EMC (EMI/EMS)	DESIGN REFER to CE				