

Item \ Model	CH1	CH2	CH3	CH4	CH5	CH6	CH7
Output Voltage	+ 3.3V	+ 5.1VD	+ 5VA	+ 12V	+ 15.5V	- 15.5V	- 5V
Output Rating(A)	0.2~3	0.1~0.8	0.05~2.5	0.01~0.1	0~0.25	0~0.25	0.1~0.3
Current Limit Tolerance	±5%						
Input Voltage	90~264 VAC						
Input Frequency	47 ~63 Hz						
Input Current (max.)	2.0A:115VAC / 1.0A:230VAC						
Inrush Current (max.)	30A:115VAC / 60A:230VAC						
Line Regulation	±2%						
Load Regulation	±2%	±2%	±5%	±5%	±5%	±5%	±5%
Ripple & Noise (max.)	50m Vp-p	50m Vp-p	50m Vp-p	120m Vp-p	150m Vp-p	150m Vp-p	100m Vp-p
Efficiency (typ.)	70%						
Over-Voltage Protection	AUTO Recovery						
Short-circuit Protection	AUTO Recovery						
Operating Tempature	0°C ~ 40°C						
Storage Tempature	- 40 °C ~ 85°C						
Safety	MEET EN60950 UL1950 CSA22.2 NO.950 FCC PART 15 CLASS B PERFORMANCE CISPER 22 CLASS B (EN55022) PERFORMANCE						
EMC (EMI/EMS)	DESIGN REFER to CE						