

LYTEC.CO

Lytec Co., Ltd.

LP5255-4 25W Multiple Output

Item \ Model	CH1	CH2	CH3	CH4	CH5	CH6
Output Voltage	5.1VD	5VA	15V	- 15V	- 5V	6.5V
Output Rating(A)	0.6~1.0	0.3~0.5	0.2~0.25	0.2~0.25	0.3~0.5	0.12~0.14
Current Limit Tolerance	±5%					
Input Voltage	90~264 VAC					
Input Frequency	47 ~63 Hz					
Input Current (max.)	2.0A:115VAC / 1.0A:230VAC					
Inrush Current (max.)	30A:115VAC / 60A:230VAC					
Line Regulation	±.2%					
Load Regulation	±2%		±6%		±5%	
Ripple & Noise (max.)	50m Vp-p		150m Vp-p		100m Vp-p	150m Vp-p
Efficiency (typ.)	70%					
Over-Voltage Protection	AUTO Recovery					
Short-circuit Protection	AUTO Recovery					
Operating Temperature	0°C ~ 50°C					
Storage Temperature	- 40 °C ~ 85°C					
Safety	MEET EN60950 UL1950 CSA22.2 NO.950 FCC PART 15 CLASS B PERFORMANCE CISPER 22 CLASS B (EN55022) PERFORMANCE					
EMC (EMI/EMS)	DESIGN REFER to CE					

Copyright © 2014 Lytec Co., Ltd. All rights reserved.

Web Site: <http://www.lytec.com.tw>

Tel:03-4807561 Fax:03-4807002 E-mail:lytec@ms37.hinet.net