

LYTEC.CO

Lytec Co., Ltd.

LP6251 25W Multiple Output

Item \ Model	CH1	CH2	CH3	CH4	CH5
Output Voltage	+ 3.3V	+ 5VA	+ 12V	- 12V	+ 5VD
Output Rating(A)	0~1.5	0~0.3	0.01~0.5	0.01~0.5	0.05~1.2
Current Limit Tolerance	±5%				
Input Voltage	90~264 VAC				
Input Frequency	47 ~63 Hz				
Input Current (max.)	2.0A:115VAC / 1.0A:230VAC				
Inrush Current (max.)	30A:115VAC / 60A:230VAC				
Line Regulation	±2%				
Load Regulation	±2%	±2%	±2%	±10%	±10%
Ripple & Noise (max.)	33m Vp-p	50m Vp-p	120m Vp-p	120m Vp-p	50m Vp-p
Efficiency (typ.)	70%				
Over-Voltage Protection	AUTO Recovery				
Short-circuit Protection	AUTO Recovery				
Operating Tempature	0°C ~ 40°C				
Storage Tempature	- 40 °C ~ 85°C				
Safety	MEET EN60950 UL1950 CSA22.2 NO.950 FCC PART 15 CLASS B PERFORMANCE CISPER 22 CLASS B (EN55022) PERFORMANCE				
EMC (EMI/EMS)	DESIGN REFER to CE				

Copyright © 2014 Lytec Co., Ltd. All rights reserved.

Web Site: <http://www.lytec.com.tw>

Tel:03-4807561 Fax:03-4807002 E-mail:lytec@ms37.hinet.net